

HARO

Sports

Datasheet Helsinki 10-10

Type: area-elastic sports floor
 Usage: sports- and multi-purpose facilities, ideal for renovations
 Underfloor heating compatible



1. HARO Premium sports parquet
2. PE-foil
3. HARO load distribution module
4. HARO elastic layer

Helsinki 10-10	Installation on an even sub-floor according to DIN 18202, 2019-07, chart 3, line 4
10 mm	HARO elastic layer, offset in joints, loosely laid out
12 mm	HARO load distribution module consisting of special plywood strips, with tongue and groove connection on the front side, with building authority approval, format: 2500 x 175 mm.
0,03 mm	PE-foil, 10 % overlapped, loosely laid out
12,6 mm	HARO sports parquet glued in tongue and groove, stapled to the load distribution module, with solid wood top layer 3.6 mm and wear-resistant, factory applied PERMADUR® sealant
34,6 mm	Construction height

Model HELSINKI 10-10 entirely meets and exceeds the EN 14904, FIBA rules 2010, DIN V 18032-2; April 2001 standards and is subject to the annual quality control RAL GZ 942. This floor has a general building authority approval.



Hamberger Flooring GmbH & Co. KG
 Rohrdorfer Straße 133, 83071 Stephanskirchen, DE
 Phone +49 8031 700-240, Fax +49 8031 700-249
 email: info@haro-sports.com, web: www.haro-sports.com