

# HARO

## Sports

### Datasheet Rome 20

Type: Mobile sports floor  
 Usage: Multipurpose, exhibition, athletics and ice rinks  
 Underfloor heating compatible



1. HARO portable floor parquet panels
2. HARO special elastic layer

Rome 20	Installation on an even sub-floor acc. to DIN 18202: 1997-04, chart 3
15 mm	HARO special elastic layer, single-sided laminated, offset at joints, loosely laid out
24,6 mm	HARO module unit with patented special locking system, consisting of: HARO sports parquet modules with solid wood overlay 3.6 mm, with abrasion-resistant, factory-applied PERMADUR® sealant, grid panels made of plywood BFU 100 according to DIN 68705, part 3; Dimensions: 91.5 x 91.5 x 12 mm and circumferential connecting latches made of special plywood BFU 100, according to DIN 68705, part 3; dimensions: 19.3 x 19.3 x 12 mm
39,6 mm	Construction height

Model ROME 20 meets and exceeds the requirements of the EN 14904, FIBA rules 2010, DIN V 18032-2; April 2001 and is subject to the annual quality control RAL GZ 942. Model ROME 20 is also subject to the Austrian standard ÖISS directive 08/2005 and has a general building authority approval.



Hamberger Flooring GmbH & Co. KG  
 Rohrdorfer Straße 133, 83071 Stephanskirchen, DE  
 Phone +49 8031 700-240, Fax +49 8031 700-249  
 email [info@haro-sports.com](mailto:info@haro-sports.com), web [www.haro-sports.com](http://www.haro-sports.com)