

HARO

Sports

Datasheet Helsinki Eco

Type: area-elastic sports floor
 Usage: sports- and multi-purpose facilities, ideal for renovations
 Underfloor heating compatible
 Installation on dry screed and thermal insulation possible



1. HARO Premium sports parquet
2. PE-foil
3. HARO load distribution strips
4. HARO elastic layer

Helsinki Eco	Installation on an even sub-floor according to DIN 18202, 2019-07, chart 3, line 4
10 mm	HARO elastic layer, offset in joints, loosely laid out
12 mm	HARO load distribution strips made of OSB, face side with tongue & groove connection, with building authority approval; dimension: 2500 x 175 mm
0,03 mm	PE-foil, 10 % overlapped, loosely laid out
13,5 mm	HARO sports parquet glued in tongue and groove, stapled to the load distribution strips, with solid wood top layer 3.6 mm and wear-resistant, factory applied PERMADUR® sealant
35,5 mm	Construction height

Model HELSINKI Eco entirely meets and exceeds the EN 14904, FIBA rules 2010, DIN V 18032-2; April 2001 standards and is subject to the annual quality control RAL GZ 942. This floor has a general building authority approval.



Hamberger Flooring GmbH & Co. KG
 Rohrdorfer Straße 133, 83071 Stephanskirchen, DE
 Phone +49 8031 700-240, Fax +49 8031 700-249
 email: info@haro-sports.com, web: www.haro-sports.com