

HARO

Sports

Datasheet Berlin 13F

Type: area-elastic sports floor
Usage: sports and multipurpose
Underfloor heating compatible



1. HARO Premium sports parquet
2. PE-foil
3. HARO counter floor
4. HARO double swing beam

	Installation from the top edge of raw concrete
54 mm	Module unit HARO double swing beam, with intermediate bars, damping element and support beams, distance centre to centre 444 mm laid out in longitudinal direction of hall
15 mm	Counter floor module distance centre to centre 122 mm fixed in transverse position on the HARO double swing beam module units. The spruce modules are artificially dried, parallel edged, planed on all sides, made in fixed lengths
0.03 mm	PE-foil, 10% overlapped, loosely laid out
12.6 mm	HARO sports parquet modules nailed to counter floor modules, sports parquet with 3.6mm solid wood layer and wear-resistant, factory applied PERMADUR® sealing
81.6 mm	Construction height

The Berlin 13F model complies with DIN V 18032-2; April 2001, EN 14904 and is subject to RAL-GZ 942 quality assurance. It also fulfils all requirements of FIBA rules 2010. This floor has general building authority approval.



Hamberger Flooring GmbH & Co. KG
Rohrdorfer Straße 133, 83071 Stephanskirchen, DE
Phone +49 8031 700-240, Fax +49 8031 700-249
email info@haro-sports.com, web www.haro-sports.com