

HARO

Sports

Datasheet Berlin 30

Type: area-elastic sports floor
Usage: sports- and multi-purpose facilities
Underfloor heating compatible



1. HARO Premium sports parquet
2. PE-foil
3. HARO counterfloor
4. HARO double swing beam

	Installation from the top edge of raw concrete
54 mm	Module unit HARO double swing beam, with intermediate bars, damping element and support beams, distance centre to centre 445 mm laid out in longitudinal direction of hall
15 mm	Counterfloor module, distance centre to centre 122 mm fixed in transverse position on the HARO double swing beam module units. The spruce modules are kiln-dried, parallel edged, planed on all sides, made in fixed lengths
0.03 mm	PE-foil, 10% overlapped, loosely laid out
15 mm	HARO sports parquet modules nailed to counter floor modules, sports parquet with 5.6mm solid wood layer and wear-resistant, factory-applied PERMADUR® sealing
84 mm	Construction height

Model Berlin 30 complies with DIN V 18032-2; April 2001 and EN 14904.



Hamberger Flooring GmbH & Co. KG
Rohrdorfer Straße 133, 83071 Stephanskirchen, DE
Phone +49 8031 700-240, Fax +49 8031 700-249
email info@haro-sports.com web www.haro-sports.com