

HARO

Sports

Datasheet Helsinki 20-10

Type: area-elastic sports floor

Usage: sports- and multi-purpose facilities, ideal for renovations

Underfloor heating compatible



1. HARO Premium sports parquet
2. PE-foil
3. HARO load distribution module
4. HARO elastic layer

	Installation on an even sub-floor according to DIN 18202, 2019-07, chart 3, line 4
10 mm	HARO elastic layer, offset in joints, loosely laid out
12 mm	HARO load distribution module consisting of special plywood strips, with tongue and groove connection on the front side, with building authority approval, format: 2500 x 175 mm
0.03 mm	PE-foil, 10 % overlapped, loosely laid out
18.3 mm	HARO sports parquet glued in tongue and groove, stapled to the load distribution module, with solid wood top layer of 5.6 mm and wear-resistant, factory-applied PERMADUR® sealant
40.3 mm	Construction height

Model HELSINKI 20-10 entirely meets and exceeds the EN 14904, DIN V 18032-2; April 2001 standards and is subject to the annual quality control RAL-GZ 942. This floor has general building authority approval.



Hamberger Flooring GmbH & Co. KG
 Rohrdorfer Straße 133, 83071 Stephanskirchen, DE
 Phone +49 8031 700-240, Fax +49 8031 700-249
 email info@haro-sports.com, web www.haro-sports.com